

# CONTROLLER Accessories

For 2001, Nelson introduced the EZ Pro<sup>™</sup> series of irrigation controllers and the EZ Command™ Radio control unit. Ideal for residential and commercial applications, these units offer superior electronics and flexible programming. Now Nelson offers a variety of accessories for the EZ Pro controller and EZ Command Radio unit making them even more flexible. Nelson's Rain-Trip™ Rain Sensor for unneeded watering, a EZ Pro™ Controller pedestal pedestal for out of the way mounting needs, the Radio module giving your EZ Pro radio capabilities with the EZ Command, and a Protective Jacket for the EZ Command for when you're out on the job site.

8000

**Pump start relay** 

8501

Rain-Trip™ Rain Sensor

8602

**EZ Command™ Radio Module** 

8607

**EZ Command™ Protective Jacket** 

# CONTROLLER Accessories

8602



#### EZ Command™ Radio Module

- Upgrades base model EZ Pro by adding radio capability
- Easy to install just plug it in!





## **EZ Command™ Protective Jacket**

- Helps protect EZ Command<sup>™</sup> against normal daily use
- Clip located on jacket for belt configuration



8501 rain sensor

#### Rain-Trip™ Rain Sensor

- Unit ready for bracket mount or ½" conduit/pipe thread mount at bottom
- Adjusts easily from 1/8" to 1" rainfall
- · Compatible with most controller brands (Ready for normally-closed or normally-open hookup)
- · Supplied with 25 feet of hookup wire
- · Saves unneeded watering
- Designed to be used with low voltage irrigation systems only



8000

# 8609

## **EZ Pro™ Controller pedestal**

- The Model 8609 EZ Pro Pedestal is designed to be used with all EZ Pro controllers. It is designed to maximize radio performance on EZ Pro radio equipped models.
- Entire front panel removable for easy access to wiring
- Made of industrial grade non-rusting stainless steel
- 35" H x 10.5" W
- Weight: 30 lbs
- · Controller mounting hardware and



## **Pump start relay**

**Box Features** 

- · Waterproof, dust proof, outdoor mount, foam seal
- Knockouts provided on all sides, 1/2" and 3/4"
- Sealing plugs provided to waterproof mounting screws Relay Features
- · Contactor UL, CSA approvals
- · No exposed parts. Contacts and coil fully enclosed
- Finger-proof construction. No additional cover needed
- Pressure wire screw terminal accepts 24 to 10 AWG wire
- Single and 3 phase. One relay will fit many applications

1 Phase - 1HP 120 volt

3 Phase - 3HP 200-240 volt

2HP 200-240 volt 3HP 440-480 volt